

EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

0075/1491/162/07/21/1217 Certificate N°

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment:

Manufacturer: **CENIGOMMA SRL**

STRADA DELL ALPO 26,37136 VERONA

Description

PPE Type: protective glove against mechanical risks

Product reference: E52.03N

Article code:

Glove description: 5 fingers glove-13 gauge grey polyester seamless, black foam nitrile

3/4 Coat, palm black nitrile dot

Available sizes: XS/6-3XL/12

Pictures:







Reference standard:

Levels of performance / class of protection

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material. « 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

EN ISO 21420:2020

EN 388:2016 + A1:2018

4121X

At the date of the certificate, the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)


Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the Instruction for Use index 01 dated from JULY 2021

NOTA: Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by **Didier GUISADO**

Certification and Quality Manager





In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective

www.ctcgroupe.com

cemarking@ctcgroupe.com

Equipment and repealing the Directive 89/686/EEC. CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France Tél.: +33 (0)4 72 76 10 10 - Fax: +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726





CENIGOMMA SRL

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product : E52.03N

Article code : /

Technical file index : 01

Last update : JULY 2021

IDENTIFICATION

Reference of the product: : E52.03N

Article code : : /

Basic Model

Technical file index: : 01

Last update : : JULY 2021

Manufacturer:

CENIGOMMA SRL STRADA DELL ALPO 26,37136 VERONA ITALY

tel: 045-8283794 fax: 045-8283794

Factory:

CENIGOMMA SRL STRADA DELL ALPO 26,37136 VERONA ITALY

tel: 045-8283794 fax: 045-8283794

GLOVE DESCRIPTION

General glove description and intended use:

5 fingers glove-13 gauge grey polyester seamless, black foam nitrile 3/4 Coat, palm black nitrile dot This glove is designed against mechanical risks.

Type of coating finish: foam

Visual description (picture back and palm sides) :



	Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)					
		Applicable	Covered by			
			✓ Standard			
§1	Requirements defined in the Annex II §1 are applicable to all PPE	✓	✓ Instruction for use			
			✓ Marking			
			Standard			
§1.4	Manufacturer's instructions and information is available	✓	✓ Instruction for use			
			Marking			
			Standard			
§2.5	PPE which may be caught up during use	✓	✓ Instruction for use			
			Marking			
	PPE bearing one or more identification markings or indicators directly or indirectly		✓ Standard			
§2.12	relating to health and safety	✓	✓ Instruction for use			
	relating to health and salety		✓ Marking			
§3.3	The PPE is intended to protect against mechanical injuries	V	✓ Standard			
			✓ Instruction for use			
			✓ Marking			

Glove constitution:

	Reference	Color	Material	Surfacic mass (g/m²)	Gauges	Thickness
Palm		BLACK	NITRILE			0.2MM
		BLACK	NITRILE DOTS			0.3MM
		GREY	POLYESTER	105g/m²	13GAUGE	
Back		GREY	POLYESTER	105g/m²	13GAUGE	
Cuff		GREY	POLYESTER/ELASTIC	135g/m2	13GAUGE	
Binding		WHITE	POLYESTER			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425. This glove is designed against mechanical risks.

It is a category II product.

GENERAL REQUIREMENTS

Standard EN ISO 21420 : 2020

Dexterity: 5

Available size XS/6-3XL/12

range:

table B.1

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Mechanical hazard EN 388 : 2016 + A1 : 2018

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	1
Tear strength resistance	2
Puncture resistance	1
Cut Resistance method (EN ISO 13997)	X
Impact Protection	-

The levels of performance have been measured on the palm.

TEST REPORTS

Laboratory	СТС	Other
EN ISO 21420 + innocuousness	S201212678_1 S200505252_1 S200605486_1	
EN 388	S200505252_1 S200505254_1	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer:

Logo (€

Glove's reference: E52.03N

Article Code: /

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer:

Date of Manufacture (month/year) and/or serial/batch number :

Date of obsolescence (month/year) if applicable:

Marking example:





Marking of packaging example:



Method of marking on the glove :

sewing label on the glove + marked on the headcard

Packaging suitable for transport:

12 PAIRS IN ONE POLYBAG, 10 POLYBAG IN ONE CARTON

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

Cleaning instructions:

The gloves are not washable.

MEANS OF CONTROL

Factory use Sampling Plan AQL 2.5 to do goods inspection; glove should meet EN ISO 21420 and EN388 test result; Glove should not be broken, thread should not be out. no hole, no mold, no scratch, Nitrile coat should even, no bubble; Goods will follow sampling plan AQL 2.5 to do lab tests, to ensure glove reach EN388 standard; each batch test need attach the testing report marked date; all results need filed in system for easy checking; Inspection staff need do double inspection work to ensure every step's records inlcuding package which meet the insturction required; Glove inspection work on EN ISO 21420 and EN388 must be tested once every year

INSTRUCTION FOR USE

CENIGOMMA SRL

STRADA DELL ALPO 26,37136 VERONA

ITALY

Glove reference: E52.03N

Article code: /

User notice index: 01

Last update: JULY 2021





Glove description:

 $5 \ \text{fingers glove-13 gauge grey polyester seamless,} \\ \text{black foam nitrile 3/4 Coat,palm black nitrile dot}$

This glove is a personal protective equipment belonging to the category II.

It meets the requirements of the PPE Regulation 2016/425: innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (0075) 4, rue Hermann Frenkel 69367 LYON Cedex 07 FRANCE

Applicable standards :

The glove meets the requirements of the standard EN ISO 21420:2020 « Protective Gloves - General requirements and test methods ».

Dexterity: 5

Available size range:

XS/6-3XL/12

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B.

Moreover, this glove has been designed for the following applications:

« X »indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Application :

Mechanical hazard - EN 388:2016 +

A1:2018



4 1 2 1 X Levels of performance



Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	2	(on 4 maxi)
Puncture resistance	1	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	Х	(A to F)
Impact Protection		

Read carefully the instructions for use provided with the product

Protection limit:

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

Before use, the glove shall be visually inspected for any defect or imperfections. In case of deterioration, the gloves must be scrapped (abrasion, cut, tear, ...).

No flame protection is claimed. This glove shall not be in contact with naked flame.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

The levels of performance against mechanical risks are only valid for the palm of the glove .

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises. The gloves are not washable.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

Declaration of conformity:

Available with product.