



EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/1491/162/08/21/1295

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : CENIGOMMA SRL
STRADA DELL ALPO 26,37136 VERONA
ITALY

Description

PPE Type : *protective glove against mechanical risks*


Product reference : ETL80.04

Article code : /

Glove description : Black Foam nitrile Palm Coat,13gauge HDPE+Steel Wire Seamless Glove

Available sizes : 6/XS-12/XXXL

Pictures :



Reference standard :

Levels of performance / class of protection

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.
« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

EN ISO 21420:2020

-

EN 388:2016 + A1:2018

4 X 4 3 E

At the date of the certificate, the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the Instruction for Use index 01 dated from AUGUST 2021

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by
Didier GUISSADO
Certification and Quality Manager

Date of first issue : 05 August 2021
End of validity date : 05 August 2026



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.



Accreditation n° 5-0594
Scope available on:
www.cofrac.fr

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir: Chaussure Maroquinerie Ganterie
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

CENIGOMMA SRL

**MANUFACTURER'S TECHNICAL FILE TO THE
PPE REGULATION 2016/425**

Reference of the product	:	ETL80.04
Article code	:	/
Technical file index	:	01
Last update	:	AUGUST 2021

IDENTIFICATION

Reference of the product :	:	ETL80.04
Article code :	:	/
Basic Model		
Technical file index :	:	01
Last update :	:	AUGUST 2021

Manufacturer :

CENIGOMMA SRL
STRADA DELL ALPO 26,37136 VERONA
ITALY

tel : 045-8283794

fax : 045-8283794

Factory :

CENIGOMMA SRL
STRADA DELL ALPO 26,37136 VERONA
ITALY

tel: 045-8283794

fax: 045-8283794

GLOVE DESCRIPTION

General glove description and intended use:

Black Foam nitrile Palm Coat, 13gauge HDPE+Steel Wire Seamless Glove
 This glove is designed against mechanical risks.
 Type of coating finish : foam

Visual description (picture back and palm sides) :



Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)			
		Applicable	Covered by
§1	Requirements defined in the Annex II §1 are applicable to all PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§1.4	Manufacturer's instructions and information is available	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.5	PPE which may be caught up during use	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§3.3	The PPE is intended to protect against mechanical injuries	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking

Glove constitution :

	Reference	Color	Material	Surfacic mass (g/m ²)	Gauges	Thickness
Palm		BLACK	Nitrile			0.2MM
		Black+White	HDPE+Steel Wire	290g/m ²	13GAUGE	
Back	3/4 coating	BLACK	Nitrile			0.2MM
		Black+White	HDPE+Steel Wire	290g/m ²	13GAUGE	
Cuff		Black+White	HDPE+Steel Wire+Elastic	330g/m ²	13GAUGE	
Binding		WHITE	POLYESTER			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.

This glove is designed against mechanical risks.
It is a category II product.

GENERAL REQUIREMENTS

Standard EN ISO 21420 : 2020

Dexterity : 5

Available size range: 6/XS-12/XXXL

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B table B.1

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Mechanical hazard EN 388 : 2016 + A1 : 2018

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	X
Tear strength resistance	4
Puncture resistance	3
Cut Resistance method (EN ISO 13997)	E
Impact Protection	-

The levels of performance have been measured on the palm.

TEST REPORTS

Laboratory	CTC	Other
EN ISO 21420 + innocuousness	S200505263_1 S201212697_1 S200605486_1	
EN 388	S200505263_1 S200505267_1 S200403679_1	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer :

Logo

Glove's reference : ETL80.04

Article Code : /

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer :

Date of Manufacture (month/year) and/or serial/batch number :

Date of obsolescence (month/year) if applicable:

Marking example :



Marking of packaging example :



Method of marking on the glove :

sewing label on the glove + marked on the headcard

Packaging suitable for transport:

12 PAIRS IN ONE POLYBAG, 10 POLYBAG IN ONE CARTON

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Cleaning instructions:

The gloves are not washable.

MEANS OF CONTROL

Factory use Sampling Plan AQL 2.5 to do goods inspection; glove should meet EN ISO 21420 and EN388 test result; Glove should not be broken, thread should not be out. no hole, no mold, no scratch, Nitrile coat should even, no bubble; Goods will follow sampling plan AQL 2.5 to do lab tests, to ensure glove reach EN388 standard; each batch test need attach the testing report marked date; all results need filed in system for easy checking; Inspection staff need do double inspection work to ensure every step's records including package which meet the instruction required; Glove inspection work on EN ISO 21420 and EN388 must be tested once every year

INSTRUCTION FOR USE

CENIGOMMA SRL
STRADA DELL'ALPO 26,37136 VERONA
ITALY

Glove reference : ETL80.04
 Article code: /
 User notice index : 01
 Last update : AUGUST 2021



Glove description :

Black Foam nitrile Palm Coat, 13gauge HDPE+Steel Wire Seamless Glove
 This glove is a personal protective equipment belonging to the category II.
 It meets the requirements of the PPE Regulation 2016/425 : innocuousness, comfort, solidity.
 It has been subject to a UE-type Examination performed by :

C.T.C. (0075)
 4, rue Hermann Frenkel
 69367 LYON Cedex 07
 FRANCE

Applicable standards :

The glove meets the requirements of the standard EN ISO 21420:2020 « Protective Gloves - General requirements and test methods ».

Dexterity: 5

Available size range: 6/XS-12/XXXL

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B.

Moreover, this glove has been designed for the following applications :

- « X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.
- « 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Application :

Mechanical hazard - EN 388:2016 + A1:2018



4 X 4 3 E
 Levels of performance



Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	X	(on 5 maxi)
Tear resistance	4	(on 4 maxi)
Puncture resistance	3	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	E	(A to F)
Impact Protection		

Read carefully the instructions for use provided with the product

Protection limit :

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.
 This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.
 The protection against risks or hazards which are not mentioned in this document is not warranted.
 These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.
 The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.
 Before use, the glove shall be visually inspected for any defect or imperfections. In case of deterioration, the gloves must be scrapped (abrasion, cut, tear, ...).
 No flame protection is claimed. This glove shall not be in contact with naked flame.
 For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.
 The levels of performance against mechanical risks are only valid for the palm of the glove.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.
 The gloves are not washable.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

Declaration of conformity :

Available with product.