

SCHEDA TECNICA INFORMATIVA

## TAPPETO GRIGLIATO PVC

	<b>REACTION TO FIRE:</b>	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2 ASTM E648-06	Class Bfl S1 ≥ 8 kw/m <sup>2</sup> Pass Type I
	<b>FLEXIBILITY:</b>	EN 435 ASTM F137	< 20mm Pass
	<b>SLIP RESISTANCE:</b>	EN 13893 DIN 51130	Class DS- R12
	<b>ABRASION RESISTANCE</b>	EN 660-2 ASTM D3384	Wear Group P Pass
	<b>RESIDUAL INDENTATION:</b>	EN 433 ASTM F970	< 0.1 mm Static load 800 psi
	<b>CASTOR CHAIR:</b>	EN 425	Continuous Use
	<b>LIGHT FASTNESS:</b>	EN 20105: B02	> Blue Wool Standard 6
	<b>WEAR LAYER THICKNESS:</b>	EN 429	0.2 mm, 0.3 mm
	<b>ELECTRICAL BEHAVIOR (body voltage):</b>	EN 1815	< 2.0 kV
	<b>ELECTRICAL RESISTANCE:</b>	EN 1081	
	<b>THERMAL RESISTANCE:</b>	ISO 8302 (EN 12664)	
	<b>DIMENSIONAL STABILITY:</b>	EN 434	<0.4 mm
	<b>STAIN and CHEMICAL RESISTANCE:</b>	EN 423	Good Resistance
	<b>SMOKE DENSITY:</b>	ASTM E 662-05	< 450
	<b>CLEAN ROOMS:</b>	ASTM F51/68	Class A non shedding Suitable for use in following classes of clean room: ISO 1466-11999 Class 4
	<b>FUNGI and BACTERIA RESISTANCE:</b>		Does not favor growth
	<b>MARITIME USAGE:</b>	IMO RES A 653 (16) IMO MSC 61(67) US Coast Guard Approved Marine Equipment Directive	Annex 1 Part 2 (Smoke & Toxicity) Part 5 (Spread of Flame) and Annex 2 (Surface Flammability / Heat Release)



BIS



RvA



Welding Rod No.  
Regor

WR 7949-201-4  
WR 7949-202-4  
WR 7949-203-4  
WR 7949-204-4  
WR 7949-205-4  
WR 7949-206-4  
WR-Clear

### GRIGLIATO PVC

**Descrizione:**

Tappeto PVC utilizzato comunemente per pavimentazioni industriali, protezione di qualsiasi superficie, disegno come immagine sotto raffigurata

**Description:**

Checked PVC flooring, suited for industrial use and general protection of surfaces.  
Design: see picture below



**CARATTERISTICHE TECNICHE TECHNICAL CHARACTERISTICS**

Superficie stampata	Moulded surface	Grigliato / Checkered
Superficie opposta	Opposite surface	Liscia/Smooth
Durezza	Hardness	70 Shore A
Temp. di esercizio	Range temperature	-15 / +40 °C

SPESORE	ALTEZZA	LUNGH.	COLORE	PESO
THICKNESS	WIDTH	LENGHT	COLOR	WEIGHT
mm	mt	mt		Kg/m <sup>2</sup>
1,5	2,00	10	grigio/ grey	2,70

