

EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/1491/162/04/24/0795

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment:

Manufacturer: Cenigomma s.r.l.

Strada dell' Alpo, 26 - 37136 Verona -

Italy

Description

PPE Type: protective glove against mechanical risks

Product reference: E43.06

Article code : /

Glove description: 5 fingers glove. Knitted synthetic glove, palm-dipped with nitrile foam for good

tactility and grip.

Available sizes: XS/6-S/7-M/8-L/9-XL/10-2XL/11

Pictures:







Reference standard:

Levels of performance / class of protection

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

EN ISO 21420:2020

EN 388:2016 + A1:2018


4131X

At the date of the certificate, the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the user instructions index 01 dated from APRIL 2024.

NOTA: Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by
William GELAS
Certification manager





Date of first issue: 18 April 2024 Date of end of validity: 18 April 2029



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.

www.ctcgroupe.com
cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France Tél.: +33 (0)4 72 76 10 10 - Fax: +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com



Cenigomma s.r.l.

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product : E43.06

Article code :

Technical file index : 01

Last update : APRIL 2024

IDENTIFICATION

Reference of the product: : E43.06

Article code: : /

Basic Model

Technical file index:

Last update: : APRIL 2024

Manufacturer:

Cenigomma s.r.l.

Strada dell' Alpo, 26 - 37136 Verona -

Italy

tel: 0039 045-8283711 fax: 0039 045-8283711

Factory:

RuDong Kai Hong Textile Product Co., Ltd

Chen Ge Zhuang Villiage, FengLi, RuDong Town

NanTong

tel: 0513 84752787

fax: /

GLOVE DESCRIPTION

General glove description and intended use:

5 fingers glove. Knitted synthetic glove, palm-dipped with nitrile foam for good tactility and grip.

This glove is designed against mechanical risks.

Type of coating finish: foam

Visual description (picture back and palm sides):



Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)				
		Applicable	Covered by	
			Standard	
§1	Requirements defined in the Annex II §1 are applicable to all PPE	\boxtimes		
			Marking	
			Standard	
§1.4	Manufacturer's instructions and information is available	\boxtimes		
		_	☐ Marking	
	PPE which may be caught up during use	\boxtimes	☐ Standard	
§2.5				
			☐ Marking	
	PPE bearing one or more identification markings or indicators directly or		Standard	
§2.12	indirectly relating to health and safety	\boxtimes		
	Indirectly relating to nealth and safety			
	The PPE is intended to protect against mechanical injuries	×	Standard Standard	
§3.3				

Glove constitution:

	Reference	Color	Material	Surfacic mass (g/m²)	Gauges	Thickness
Dalas	coating	Black	Nitrile			0.2mm
Palm	liner	Gray	Nylon + spandex	175 g/m2	15	
Back	liner	Gray	Nylon + spandex	175 g/m2	15	
Cuff		Gray/ white	nylon/ spandex/ elastic	220 g/m2	15	
Binding		white	polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.

This glove is designed against mechanical risks.

It is a category II product.

GENERAL REQUIREMENTS

Standard EN ISO 21420 : 2020

Dexterity: 5

Available size range: XS/6 - S/7 - M/8 - L/9 - XL/10 - 2XL/11

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B table B.1

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

- « X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.
- « 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Mechanical hazard EN 388:2016 + A1:2018

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	1
Tear strength resistance	3
Puncture resistance	1
Cut Resistance method (EN ISO 13997)	X
Impact Protection	N/A

The levels of performance have been measured on the palm.

TEST REPORTS

Laboratory	CTC	Other
EN ISO 21420 + innocuousness	S231111351_2 S231111264_1	
EN 388	S231111351_2 S231211917_1	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer:

Logo (€

Glove's reference: E43.06

Article Code : /

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer:

Date of Manufacture (month/year) and/or serial/batch number :

Date of obsolescence (month/year) if applicable:

Marking example :





Method of marking on the glove :

Marking on sewn tag, headcard and sticker

Packaging suitable for transport:

each glove with colored headcard, 12 pairs/ per transparent polybag, 120 pairs (10 polybags) each carton

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

<u>Cleaning instructions:</u>

The gloves are not washable.

MEANS OF CONTROL

Plant produces gloves follow EN ISO 21420 and EN388 Standard; Each step from material purchase, knitting, dipping work, inventory management, Inspection, has detail record. Sampling plan follow AQL1.5; Plant set test interor lab, which handle and monitor glove quality meeting EN ISO 21420, EN 388 standard; Test frequence is test of abrasion resistance for each shift every day; For Cut resistance requirement glove, test will be handled each order before mass production; Tear and puncture test will be operated each order.

INSTRUCTIONS FOR USE

Cenigomma s.r.l.

Strada dell' Alpo, 26 - 37136 Verona -

Italy

Glove reference: E43.06

Article code: /

User notice index: 01

Last update: APRIL 2024

Glove description:

5 fingers glove. Knitted synthetic glove, palm-dipped with nitrile foam for good tactility and grip. This glove is a personal protective equipment belonging to the category II.

It meets the requirements of the PPE Regulation 2016/425: innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (0075) 4, rue Hermann Frenkel 69367 LYON Cedex 07

FRANCE

The glove meets the requirements of the standard EN ISO 21420:2020 « Protective Gloves - General requirements and test methods ».

Dexterity: 5

Available size range: XS/ 6 - S/ 7 - M/ 8 - L/ 9 - XL/ 10 - 2XL/ 11

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B.

Information about marking

- « X »indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.
- « 0 » indicates that the glove falls below the minimum performance level for the individual hazard.



The CE marking means that this product meets the requirements of the regulation 2016/425

Mechanical hazard - EN 388:2016 + A1:2018



Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	3	(on 4 maxi)
Puncture resistance	1	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	Х	(A to F)
Impact Protection		



Read carefully the instructions for use provided with the product

Protection limit:

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

Before use, the glove shall be visually inspected for any defect or imperfections. In case of deterioration, the gloves must be scrapped (abrasion, cut, tear...)

No flame protection is claimed. This glove shall not be in contact with naked flame.

 $For gloves \ with \ two \ or \ more \ layers \ the \ overall \ classification \ does \ not \ necessarily \ reflect \ the \ performance \ of \ the \ outermost \ layer.$

The levels of performance against mechanical risks are only valid for the palm of the glove.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

The gloves are not washable.

PPE subject to ageing:

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

Declaration of conformity:

Available with product.



